

History Of Tabesh Tablo Shargh Company



T.T.SH CO.

with the use of :

- the modern machinery tools
- experience under the supervision of expert
- With professional engineers in consulting, design, manufacturing of switchboards
- Based on latest global standards
- by having interior and international trading facilities
- Cooperating in the international control and power distribution project.
- Member of association guild manufacture of electrical boards













CNC machinery



Mechanical unit area is 1500 m2 That contains advanced machinery



with out the slightest error Ability to punching the sheet to 2m Length

Punching is performed by the METALX Program



CNC Press Break

puma y/

11 1 ----

YZ

Bending machine capable of bending up to 3m wide



Welding Unit

• Welding types:

1116

- Welding point
- Co2 welding



Painting Grill



Electrostatic color that blows the powder to the product and enters the furnace













 The storage area is more than 3000m2 which the parts are located on its special sheleves



warehouse



The main warehouse contains raw-materials and manufactured products.

Department



- Technical Engineering Department space is 500 m.
- With cooperation of expert engineer.

Assembly Unit



 The assembly unit is located at high discipline situation and space is more than 1500 m₂.







All punches and bends are done with precision machines.

QC – HV LAB



- Power frequency test:
- Apply voltage 50-100 KV for one minute
- Impulse test : Apply voltage up to 100kv at specified time

Prefabricated compact substation



MV	OS/OS/Mg/FS	SARE
TR	800KVA	Low
LV	MCCB 1250A	HYUNDAI

EL (Italy)

Loss-AB'

(South Korea)



-Prefabricated body post fully bolted to the floor and connected to the ground. -It is easy to assemble and dismantle on a foundation.



-In the design of the body ,the city's beauty and look have been taken in to consideration.

-The lower body of the base is made of hot galvanized and corrosion resistant the walls are made of an oil-filled with electrostatic furnace Paint



The compact substation is asset of transformers, low voltage switchgear and medium voltage switchgear

Input voltage is 20KV and output voltage is 380V which is compressed to chamber which used In balding , factories , urban and rural construction centers ,mines to supply energy these type of sub stations are produced in capacities of 200 to 1600 KA it is ground -based and on a foundation .



PFS. is installed and designed according to the geographical location of the site the post layout plan will be reviewed depending on the location map to be able to access the smallest (in terms of .size) mode of access and also choose in terms of economical

Technical parameters

Rating				
Nom. Operating voltage	6.6	20		
Rated Max. voltage	12	24		
Rated power frequency	50	50		
Rated continuous current	200-2500	200-2500		
Rated lighting impulse with stand	95	95		
Internal Arc current/1s	20	20		
Enclosure thermal class	10	10		
MV/LV compartment protection Degree	4x	4x		
Transformer compartment protection Degree	23D	23D		
Enclosure type	Steel	Steel		
MV component	AIS	AIS		
LV component	CB/LBS	CB/LBS		
standards	IEC202-62271			



Low voltage switchgear with IP43



 Protecting these boards against objects larger than one millimeter

Low voltage switchgear with IP54



 Protection against water pressure at the pressure of 100 KPA • And protection against objects larger that 1 millimeter





Wall panels

- MCB , MCCB :
- SCHNEIDER
- Out door use
- With IP54



Wall panels



 Wall panels are designed and manufactured in different size and design



 Performance planning control system

 Ability to control and monitor all points of delivery under control via net work



Capacitor panel

- Features:
- Custom design
- Ability to install different kind of
- measuring devises
- for use in factories



Explosion proof boxes

- Construction:
- Single or multi enclosure panels are built to customer specifications.

- Enclosure:
- Copper free Aluminum alloy suitable for petroleum and marine locations. Cast iron on request.
- IP rating:
- Up to IP65 and IP66 to IEC 529. IP67 supplied on request.



